

**FOR MORE INFORMATION OR DRAWINGS PLEASE CONTACT THE FACTORY
H2W TECHNOLOGIES, INC. 888-702-0540 or info@h2wtech.com**

	Model #	Stroke	Continuous Force	Peak Force	Km	OD	Housing Length
		inches	Pounds (lbs)	Pounds (lbs)	lbs/(watt) ^{.5}	inches	inches
		millimeters	Newtons (N)	Newtons (N)	[N/(watt) ^{.5}]	millimeters	millimeters
1	NCC01-04-001-1X	0.125	0.06	0.18	0.08	0.44	0.36
		3.2	0.3	0.8	0.36	11.1	9.0
2	NCC01-05-001-2S	0.070	0.11	0.33	0.15	0.54	0.72
		1.2	0.5	1.5	0.67	13.7	18.3
3	NCC01-07-001-1R	0.118	0.15	0.45	0.14	0.69	0.48
		3.0	0.7	2.0	0.62	17.5	12.2
4	NCC01-09-001-1NH	0.125	0.11	0.34	0.12	0.90	0.58
		3.2	0.5	1.5	0.53	22.9	14.7
5	NCC02-07-001-1R	0.20	0.11	0.33	0.26	0.69	0.48
		5.1	0.5	1.5	1.16	17.5	12.2
6	NCC02-13-008-1R	0.50	0.80	2.40	0.45	1.25	1.00
		12.7	3.6	10.7	2.00	31.8	25.4
7	NCC02-15-015-1SA	0.16	1.5	4.5	0.66	1.49	1.00
		4.1	6.7	20.0	2.94	37.8	25.4
8	NCC03-07-001-1V	0.25	0.12	0.36	0.19	0.74	0.45
		6.4	0.5	1.6	0.85	18.8	11.4
9	NCC03-14-010-1SL	0.28	1.00	3.00	0.36	1.45	1.65
		7.1	4.5	13.4	1.60	36.8	41.9
10	NCC03-15-050-2X	0.25	5.00	15.00	1.38	1.50	1.63
		6.4	22.3	66.8	6.14	38.0	41.3
11	NCC03-16-015-2R	0.25	1.5	4.5	0.40	1.63	1.63
		6.4	6.7	20.0	1.78	41.4	41.4
12	NCC03-57-500-2X	0.31	50.0	150	5.55	5.75	4.00
		7.9	222.5	667.5	24.70	146.0	101.6
13	NCC04-10-005-1X	0.40	0.5	1.5	0.44	0.98	0.65
		10.2	2.2	6.7	1.96	25.0	16.5
14	NCC05-11-011-1X	0.50	1.1	3.3	0.67	1.20	1.10
		12.7	4.9	14.685	2.98	30.5	27.9
15	NCC05-18-060-2X	0.50	6.0	18.0	1.78	1.80	1.95
		12.7	26.7	80.1	7.92	45.7	49.5
16	NCC06-08-005-2X	0.6	0.9	2.6	0.50	0.81	1.65
		15.2	3.78	11.3	2.23	20.6	41.9
17	NCC06-60-500-1X	0.64	50	150	5.50	5.50	2.50
		16.3	222.5	667.5	24.48	139.6	63.5
18	NCC08-34-350-2X	0.80	35	105	5.80	3.35	3.40
		20.3	155.8	467.3	25.81	85.1	86.4
19	NCC09-39-190-1V	0.94	19.6	58.7	2.9	3.92	1.72
		23.9	87.2	261.2	12.91	99.6	43.7
20	NCC10-15-023-1X	1.00	2.3	6.9	0.85	1.50	1.91
		25.4	10.2	30.7	3.78	38.1	48.5
21	NCC10-15-027-1RC	1.00	2.7	7.0	0.85	1.50	2.75
		25.4	12.0	31.2	3.78	38.1	69.9
22	NCC10-30-108-1H	1	10.8	32.4	2.5	2.98	1.60
		25.4	48.06	144.18	11.13	75.6	40.6
23	NCC10-34-350-2BEI	1.00	35	105	5.6	3.00	3.50
		25.4	155.8	467.3	24.92	76.2	88.8
24	NCC12-60-1000-2X	1.20	100	300	11.8	5.60	6.50
		30.5	445	1335	52.51	142.2	165.1
25	NCC20-18-020-1X	2.00	2.0	6.0	0.75	1.75	2.75
		50.8	8.9	26.7	3.34	44.5	69.9
26	NCC20-15-027-1RC	2.00	2.7	7.0	0.65	1.5	3.75
		50.8	12.0	31.2	2.89	38.1	95.3
27	NCC34-16-020-1X	3.35	2.0	6.0	0.36	1.57	3.94
		85.1	8.9	26.7	1.60	39.9	100.1
28	NCC52-20-020-1X	5.20	2.0	6.0	0.54	2.00	5.90
		132.1	8.9	26.7	2.40	50.8	149.9

**FOR MORE INFORMATION OR DRAWINGS PLEASE CONTACT THE FACTORY
H2W TECHNOLOGIES, INC. 888-702-0540 or info@h2wtech.com**